



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : A61F 9/04 // A62B 7/12 A62B 18/02	A1	(11) International Publication Number: WO 91/18569 (43) International Publication Date: 12 December 1991 (12.12.91)
-------------------------------------------------------------------------------------------------	----	-------------------------------------------------------------------------------------------------------------------------------

(21) International Application Number: PCT/FI91/00174

(22) International Filing Date: 31 May 1991 (31.05.91)

(30) Priority data:
902746 1 June 1990 (01.06.90) FI(71) Applicant (for all designated States except US): KEMIRA
OY [FI/FI]; P.O. Box 44, SF-02271 Espoo (FI).

(72) Inventors; and

(75) Inventors/Applicants (for US only): VIENAMO, Teppo, Ta-
pani [FI/FI]; Mechelininkatu 1 B 19, SF-00180 Helsinki
(FI). SAARI, Pauli, Juhani [FI/FI]; Venesaarentie, SF-
61520 Lehmäjoki (FI). HOLMLUND, Timo, Erkki [FI/
FI]; Kytömaanpolku 3 B 6, SF-65280 Vaasa (FI). JÄR-
VINEN, Jyrki, Hannu, Veli [FI/FI]; Kustaalantie 4, SF-
65230 Vaasa (FI).(74) Agent: BERGGREN OY AB; P.O. Box 16, SF-00101 Hel-
sinki (FI).


(81) Designated States: DE, GB, SE, US.

Published
With international search report.

(54) Title: FACE SHIELD

(57) Abstract

A face shield comprising a frame (1), a glass (2) attached to the frame, a padding (3) between the frame and the face and an attaching portion, for example, a ribbon (4) encircling the head, and to which face shield air is led. The frame is hollow so that the air led into the face shield is directed into the hollow frame and the frame comprises openings through which the air is discharged inside the face shield.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SN	Senegal
CI	Côte d'Ivoire	LJ	Liechtenstein	SU	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TG	Togo
DE	Germany	MC	Monaco	US	United States of America
DK	Denmark				

Face shield

The present invention relates to a face shield comprising a frame, a glass attached to the frame, a padding between
5 the frame and the face and an attachment portion, like a ribbon encircling the head, and into which face shield air is led.

Known, so called whole face masks of this type made of
10 rubber, comprising regulating valves and fastened by ribbons hurt and are heavy as well as expensive to make. Because of the weight they have to comprise 4 to 5
buckles, whereby they are difficult to put on. Especially
15 weldings masks, into which air is led through canals, are often very heavy and the portions encircling the head are usually made of hard plastic. The big dimensions
complicate use and edge sealing is difficult to
accomplish. So called hoods made of, for example, plastic
20 cloth, paper or plastic are reasonably priced, but difficult to use and in case of an accident they may lead to risk of suffocation.

The aim of the invention is to achieve a new type of face
shield which is easy to use as well as light. The face
25 shield according to the invention is characterized by the frame being hollow so that the air directed to the face shield is directed to the hollow frame, and that the frame comprises openings through which the air is
discharged into the face shield. Said face shield is
30 intended for use with a blowing device or compressed air. The hollow frame made of light and flexible plastic yields according to the shape of the face and is of such a size that the mouth, nose and eyes will stay inside the frame. Because the shield is blow moulded, the cheapest
35 plastic qualities may be used as raw materials and, in addition, all essential parts are formed in one stage of operation. The face shield comprises a few parts which

5 makes it reasonably priced and light. Due to the form and lightness of the construction it is possible to use a fastening ribbon known from sports glasses, which ribbon is easier to handle than the previously used groups of ribbons comprising two or more ribbons.

10 By placing press buttons or other suitable fastening means in the frame it is possible to attach an additional shield made of textile, plastic or paper and covering the surface of the head remaining outside the frame. Due to the new structure of the face shield the dimensions of it are such that a hardhat, hearing protectors or even a welding mask may easily be used simultaneously with it. There is also room for spectacles inside the face shield.

15 One embodiment of the invention is characterized in that the openings are elongated slots located at the sides of the frame and are directed towards the glass so that the air is discharged in front of the face to be breathed and simultaneously to blow away possible mist from the inner surface of the glass. Thus enough air is achieved for both breathing and removing mist even when the wearer of the face shield breathes heavily or speaks.

25 Another embodiment of the invention is characterized in that the padding between the frame and the face consists of a foam plastic with open cells so that the air, which has been led in to be breathed can together with the exhalation air exit through said padding from inside the face shield. Overpressure is constantly kept up in the face shield so that there is a continuous air flow through the padding. The padding portion can be manufactured in such a way that it can be easily changed in order to maintain hygienic demands. It can, for example, contain a tape attachment. The replaceable paddings may be of different size and thickness, whereby the best fitness is achieved for faces of different

sizes.

The invention will be described in the following with reference to the enclosed drawings, in which

5 figure 1 is a diagonal front view of the face shield, figure 2 is a side view of the face shield, and figure 3 is a sectional view of the face shield.

10 The face shield comprises a frame 1, a glass 2 attached to the frame, a padding 3 located between the frame and the face and a ribbon 4, which is tightened around the head. Air is led into the face shield through a hose 5. The frame 1 is hollow so that the air led into the face shield is directed into the hollow frame and the frame 1
15 comprises openings 6, through which the air is discharged into the face shield. The openings 6 are elongated slots located at the sides of the frame 1 and directed towards the glass so that the air is discharged in front of the face to be breathed and simultaneously to blow away
20 possible mist from the inner surface of the glass. The padding 3 between the frame 1 and the face consists of a foam plastic with open cells so that the air, which has been led in to be breathed can together with the exhalation air exit through said padding from inside the
25 face shield.

Especially in connection with a blowing device and also with compressed air a face shield of this type is needed, which is easy to use, light and not expensive. The
30 padding does not necessarily have to be according to the example, it may also have closed cells or in some other way air impermeable, whereby the extra air is removed through a separate exit opening. In this case glass does not mean glass material but a transparent shield plate,
35 which in reality is transparent plastic or so called plexiglass.

Claims

1. A face shield comprising a frame (1), a glass (2) attached to the frame, a padding (3) between the frame and the face and an attaching portion, for example, a ribbon (4) encircling the head, and to which face shield air is led, characterized in that the air led into the face shield is directed into the hollow frame (1), and that the frame comprises openings (6) through which the air is discharged inside the face shield.

2. A face shield according to claim 1, characterized in that the openings (6) are elongated slots located at the sides of the frame (1) and directed towards the glass (2) so that the air is discharged in front of the face to be breathed and simultaneously to blow away possible mist from the inner surface of the glass.

3. A face shield according to claim 1, characterized in that the padding (3) between the frame and the face consists of a foam plastic with open cells so that the air, which has been led in to be breathed can together with the exhalation air exit through said padding from inside the face shield.

1/2




Fig.1

1/2




Fig.1

2/2




Fig. 3





Fig. 2

INTERNATIONAL SEARCH REPORT

International Application No PCT/FI 91/00174

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) ⁶		
According to International Patent Classification (IPC) or to both National Classification and IPC		
IPC5: A 61 F 9/04 // A 62 B 7/12, 18/02		
II. FIELDS SEARCHED		
Minimum Documentation Searched ⁷		
Classification System	Classification Symbols	
IPC5	A 61 F; A 62 B	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in Fields Searched ⁸		
SE,DK,FI,NO classes as above		
III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹		
Category [*]	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
A	SE, B, 354416 (OY ESAB) 12 March 1973, see the whole document --	1
X	SE, B, 455158 (MAREK BLASIAK) 27 June 1988, see page 2, line 22 - line 33; figure 2 --	1-3
A	DE, B, 1265342 (HENDRIK JOHANNES CORNELIS HANNEMA) 4 April 1968, see figure 1; claim 1 --	1
A	DE, A1, 2932348 (DAIMLER-BENZ AG) 26 February 1981, see page 4, line 24 - page 5, line 15 --	1
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>[*] Special categories of cited documents: ¹⁰</p> <p>^{"A"} document defining the general state of the art which is not considered to be of particular relevance</p> <p>^{"E"} earlier document but published on or after the international filing date</p> <p>^{"L"} document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>^{"O"} document referring to an oral disclosure, use, exhibition or other means</p> <p>^{"P"} document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 45%;"> <p>^{"T"} later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>^{"X"} document of particular relevance, the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>^{"Y"} document of particular relevance, the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>^{"&"} document member of the same patent family</p> </div> </div>		
IV. CERTIFICATION		
Date of the Actual Completion of the International Search		Date of Mailing of this International Search Report
3rd September 1991		1991 -09- 09
International Searching Authority		Signature of Authorized Officer
SWEDISH PATENT OFFICE		 Leif Karnsäter